

## MODEL 150 H.O. - V6

## SPECIFICATIONS



Model	a. E150DHL b. E150HSL
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White
Weight kg (lbs)	190 (419)
Engine Type	Loop Charged V6 60° E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.600 x 2.588)
Displacement cc (cu in)	2592 (158)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	Factory Tuned for High Performance
Full Throttle Operating Range	4850-5850 RPM
Gear Ratio	a. / b. 1.86:1 High Speed
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 3 STAR European Union



\* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

\*\* 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.